

HAMMER 2 EQ™



Owner's Manual

WARNING!

Before you start your new HAMMER-EQ please read the following:

ANY real tube product is sensitive to a high SPL environment. This may cause microphonics in a recording situation. Make sure you are able to shock mount and or place the unit in isolation if need be. Direct light will also affect tubes as well.

PLEASE be sure to have at least one rack space between any tube products from the product above and below the unit. This will ensure your tube unit will not over heat. Over heating will cause damage to the tubes and shorten their life span. If possible, place the HAMMER unit in the top rack space to allow air flow.

If you have received your unit via UPS/Fed-Ex/DHL, or any other courier, your HAMMER should have been double boxed for protection. If it was not double boxed, please contact your dealer and return the unit to them for a replacement.

We demand ALL our units to be double boxed to help prevent damages during shipping.

Thank you,

Peter Montessi President A Designs Audio

LEGAL NOTICE:

Fill out and Return Warranty Card to A Designs. Warranty begins the day of purchase. Your name will be placed on our mailing list (unless otherwise requested) for future updates and new product announcements.

A Designs reserves the right to make improvements or changes at any time to this product.

Published by: A Designs Audio

P.O. Box 4255

West Hills, CA 91304 U.S.A. Edition 1.0 2004 Copyright 2013 A Designs Audio, All Rights Reserved.

WARNING: Removing Cover Will Void Your Warranty.

1 Year Limited Warranty Internal Parts, 30-Day Limited Warranty Labor, 30-Day Limited Warranty Tubes

A Designs warrants that our hardware conforms substantially to the specifications contained in this manual when used in accordance these specifications for a period of 1 year from the date of original purchase from A Designs or its authorized dealers. In case of a valid warranty claim, your sole and exclusive remedy and A Designs' entire liability under any theory of liability will be, at its option, to repair or replace the product without charge, or, if not possible, to refund the purchase price to you. The warranty is not transferable and applies only to the original purchaser of the product.

For warranty service, contact A Designs Audio at 818-716-4153 to obtain a Return Merchandise Authorization (RMA) number. After obtaining the RMA number, ship defective product to A Designs Audio, P.O. Box 4255, West Hills, CA 91304. Write RMA number on outside of shipping box. Be sure to include your name, address, phone number, copy of original sales invoice and detailed description of the problem. A Designs Audio will not accept responsibility for loss or damage in shipping.

Warranty is void if product serial numbers have been removed or if the product has been damaged by abuse or unauthorized modification and repair. There are no user serviceable parts inside.

THIS WARRANTY IS IN LIEU OF ALL WARRANTIES WHETHER ORAL OR WRITTEN, EXPRESSED OR IMPLIED. A DESIGNS AUDIO MAKES NO OTHER WARRANTY EITHER EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANT ABILITY, UNLESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT. PURCHASERS SOLE AND EXCLUSIVE REMEDY UNDER THIS WARRANTY SHALL BE REPAIR OR REPLACEMENT AS SPECIFIED HEREIN.

IN NO EVENT WILL A DESIGNS AUDIO BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCREMENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT IN THE PRODUCT, INCLUDING LOST PROFITS, DAMAGE TO PROPERTY AND, TO THE EXTENT PERMITTED BY LAW, DAMAGE FOR PERSONAL INJURY, EVEN IF A DESIGNS AUDIO HAS BEEN ADVISED OF THE POSSIBILITIES OF SUCH DAMAGES.

A Designs, A Designs Audio, HAMMER 2EQ is a trademark of A Designs. All other trademarks are the property of their respective owners.

Introduction

Welcome to the Analog Sound of the HAMMER 2-EQ. This is an all tube product, and there are some basics you should come to understand before using this product for the first time.

Tubes are a component that have specialized and unique features. If you are a "pre" or baby boomer, born before 1957, you may recall using tubes in various products, such as radios, amplifiers, and televisions. So, this is just to refresh your memory. If you are a "post" baby boomer, this could be your first experience with tubes, so please pay close attention! (You will be tested at the end of this manual).

Tubes are most efficient and effective when "warmed up." This means, upon starting the HAMMER 2-EQ, you should allow the tubes to become fully heated before attempting to operate. The minimum amount of warm up time is approximately 15 to 20 minutes.

Set up your instrumentation layout before powering up the HAMMER 2-EQ. Plug in your instrument or microphone while the unit is off. This will prevent unwanted noise such as "pops." The same applies when you shut down. Allow a minimum of 25 seconds for the power to drain from the tubes properly. Then you can unplug your instrument or microphone.

Placing the HAMMER 2-EQ in a rack, we recommend using the first tier or allow one x space in order to properly ventilate. Avoid overheating! Too much heat will reduce the life-span of your tubes. We also recommend strongly that you observe SPL and shock mount any tube product.

A Designs Audio has scoured the earth for the perfect combination of tubes for this unique quality sound. Go ahead, get started. Read the following pages carefully to become acquainted with the warmth and clarity that the HAMMER-EQ can deliver to your recordings.

Please feel free to email A Designs via the website with any creative applications for the use of the HAMMER 2-EQ. We have included some applications in this manual. We may just include your suggestion on our website!

Congratulations on the purchase of your HAMMER 2-EQ! Most of all have fun.

Peter Montessi, President

A Designs Audio Inc.

Hammer 2-EQ[™] Owner's Manual 3

Features

- · Vacuum-tube design hybrid
- · 2 Hard Pass Switches
- · Two (2) High Cut Switches
- Two (2) Low Cuts Switches
- Two (2) Mono Three Band EQ Sections
- · Milled Aluminum Face Plate
- Blue Jewel Lamp (Power Indicator)
- Two (2) XLR Input Connectors
- Two (2) XLR Output Connectors
- Two (2) U-Rack Space
- Two (2) 12AT7 Tubes
- · Clean and airy high end
- · Warmth, transparency, and quality sound
- Toroid Power Transformer
- · Metal Casing
- · Milled Aluminum Knobs
- Heavy Duty Carling Toggle Power Switch
- Each Cut and Boost for each side have dented pots.

In line with our company policy of continuous development, the above features are subject to change without notice.

4 | Hammer 2-EQ™ Owner's Manual

Specifications

TECHNICAL DATA

 Noise Floor.
 -94dbm with a 30KHz Bandwith

 Frequency Response
 -3dB points are 5Hz and 40KHz

 Low Boost
 +13dB

 Low Cut
 -13dB

 High Boost
 +13dB

 High Cut
 -13dB

 Low Pass
 84Hz

 High Pass
 8Khz

 Floating
 "Q"

 Distortion
 +4dbm

 Power Requirements:
 120/230 VAC - 42 Watts

 Dimensions (W x H x D)
 19" x 3.5" x 10"

 Weight
 10 lbs.(Shipping weight 12 lbs.)

In line with our company policy of continuous development, the above specifications are subject to change without notice.

The HAMMER is a 2RU rack space unit that fits nicely into any Studio Rack and will compliment your array.

UNIT SIZE:

Width: Standard 19 inches for easy Rack Mount installation.

Height: Standard 3.50 inches or 2RU Rack Space.

Depth: 10 inches
Weight: 10 lbs.

Hammer 2-EQ[™] Owner's Manual 5

Functions

Front



- 1 By-pass Switch
- 2 Hi Cut Switch
- 3 Low Cut Switch
- 4 Cut/Boost Knob For Low Frequency
- 5 Cut/Boost Knob For Mid Frequency
- 6 Cut/Boost Knob For Hi Frequency
- **T** Low Frequency Switch (30/60/125/Shelves.....30, 50, 100, 200, 300, 400, 470, 560)
- **8** Mid Frequency Switch (125, 175, 250, 500, 800, 1.2k, 1.6k, 2k, 2.7k, 3.3k, 3.9k, 4.7k)
- **9 High Frequency Switch** (1.8k, 2.5k, 3.5k, 5k, 7.5k, 10k, 15k, 20k, 40k.....4.8k, 12.5k, 30k Shelves)
- 10 Power Indicator Light
- 11 Power Switch

6 Hammer 2-EQ™ Owner's Manual

Functions (continued)

Back




- **12** AC Power Connector
- 13 Fuse Box
- 14 Fuse Amperage
- **15** XLR Outputs (balanced)
- **16** XLR Inputs (balanced)
- 17 Serial Number

Hammer 2-EQ™ Owner's Manual | 7

Recall Sheet

ALWAYS USE GOOD COMMON SENSE WHEN OPERATING ANY ELECTRONIC EQUIPMENT.

IF YOU HAVE QUESTIONS, PLEASE CONTACT YOUR DEALER OR THE MANUFACTURER BEFORE DOING ANYTHING!!!!!





A-DESIGNS AUDIO INC. PRO-AUDIO

P.O. Box 4255
West Hills, CA 91304 USA (818) 716-4153
www.adesignsaudio.com

8 | Hammer 2-EQ™ Owner's Manual